

# เครื่องคลายม้วน ดัดเรียบ รุ่น GO



## Description

1. Decoiler and straightener two in one style can save installation space, lower transition procedure.
2. The Decoiler and straightener are controlled separately by independent electricity boxes.
3. Straightener adopts the cardan joint and gear transmission.
4. The straightening gear adopts the dial indicator and is able to find out the leveling up point rapidly.
5. The additional back pressure wheel enables the straightening result much better.
6. The additional lubrication system prolonged the machine life span.

## TECHNICAL SPECIFICATIONS

Technical Parameter	GO-200	GO-300	GO-400	GO-500	GO-600
Maximum coil width	200mm	300mm	400mm	500mm	600mm
Material thickness	0.3-2mm	0.3-2mm	0.3-2mm	0.3-2mm	0.3-2mm
Expansion range	450mm-530mm	450mm-530mm	450mm-530mm	450mm-530mm	450mm-530mm
Coil weight capacity	2000kg	2000kg	3000kg	3000kg	4000kg
Speed	15m/min	15m/min	15m/min	15m/min	15m/min
Coil Outside diameter	Maximum 1200mm				
Main shaft	40Cr	40Cr	40Cr	40Cr	40Cr



## Feature Decoiler and Straightener 2 in 1 Machine

